

ODYSSEY QUOTE WORDING

Copy / Paste into quote body

The highlighted field must be changed to match the application conditions

DS015 – 5 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 200 psig discharge pressure at 1,500 SCFH flow

Skid mounted AN3.4A compressor, single stage, air-cooled
5 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC and HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 50”L x 46”W x 46”H, 700 lbs

DS026 – 7.5 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 200 psig discharge pressure at 2,640 SCFH flow

Skid mounted AN6A compressor, single stage, air-cooled
7.5 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC and HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 50”L x 46”W x 46”H, 775 lbs

DS033 – 10 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 400 psig discharge pressure at 2,640 SCFH flow

Skid mounted 2AN10C compressor, two stage, air-cooled
10 TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled intercooler, mounted with pressure relief valve
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 50”L x 46”W x 48”H, 850 lbs

DS033 – 15 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 400 psig discharge pressure at 2,640 SCFH flow

Skid mounted 2AN10C compressor, two stage, air-cooled

15 TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz

Motor contactor & overload protection

V-belt drive and belt guard

Air cooled intercooler, mounted with pressure relief valve

Air cooled aftercooler, mounted with pressure relief valve

Control panel with PLC with HMI touch screen

On screen pressure, temperature, and fault readings

Fully automatic compressor load/unload

E-Stop push button

Pressure transducers and RTD

Size/Weight: 50”L x 46”W x 48”H, 850 lbs

DS044 – 10 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 300 psig discharge pressure at 4,440 SCFH flow

Skid mounted AN10C compressor, single stage, air-cooled

10 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz

Motor contactor & overload protection

V-belt drive and belt guard

Air cooled aftercooler, mounted with pressure relief valve

Control panel with PLC with HMI touch screen

On screen pressure, temperature, and fault readings

Fully automatic compressor load/unload

E-Stop push button

Pressure transducers and RTD

Size/Weight: 50”L x 46”W x 48”H, 900 lbs

DS044 – 15 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 300 psig discharge pressure at 4,440 SCFH flow

Skid mounted AN10C compressor, single stage, air-cooled

15 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz

Motor contactor & overload protection

V-belt drive and belt guard

Air cooled aftercooler, mounted with pressure relief valve

Control panel with PLC with HMI touch screen

On screen pressure, temperature, and fault readings

Fully automatic compressor load/unload

E-Stop push button

Pressure transducers and RTD

Size/Weight: 50”L x 46”W x 48”H, 900 lbs

DS060 – 20 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 400 psig discharge pressure at 4,200 SCFH flow

Skid mounted 2AN15D compressor, two stage, air-cooled
20 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled intercooler, mounted with pressure relief valve
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 52”L x 46”W x 54”H, 1400 lbs

DS060 – 25 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 400 psig discharge pressure at 4,200 SCFH flow

Skid mounted 2AN15D compressor, two stage, air-cooled
25 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled intercooler, mounted with pressure relief valve
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 52”L x 46”W x 54”H, 1400 lbs

DS081 – 25 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 500 psig discharge pressure at 7,950 SCFH flow

Skid mounted 2AN22E compressor, two stage, air-cooled
25 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled intercooler, mounted with pressure relief valve
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 56”L x 54”W x 58”H, 2000 lbs

DS081 – 30 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 500 psig discharge pressure at 7,950 SCFH flow

Skid mounted 2AN22E compressor, two stage, air-cooled
30 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled intercooler, mounted with pressure relief valve
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 56”L x 54”W x 58”H, 2000 lbs

DS081 – 40 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 500 psig discharge pressure at 7,950 SCFH flow

Skid mounted 2AN22E compressor, two stage, air-cooled
40 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled intercooler, mounted with pressure relief valve
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 56”L x 54”W x 58”H, 2000 lbs

DS087 – 20 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 250 psig discharge pressure at 8,150 SCFH flow

Skid mounted AN20D compressor, single stage, air-cooled
20 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 52”L x 46”W x 56”H, 1100 lbs

DS087 – 25 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 250 psig discharge pressure at 8,150 SCFH flow

Skid mounted AN20D compressor, single stage, air-cooled
25 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 52”L x 46”W x 56”H, 1100 lbs

DS133 – 40 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 400 psig discharge at 12,000 SCFH flow

Skid mounted 2AN38F compressor, two stage, air-cooled
40 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled intercooler, mounted with pressure relief valve
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 86”L x 74”W x 76”H, 2900 lbs

DS133 – 50 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 400 psig discharge at 12,000 SCFH flow

Skid mounted 2AN38F compressor, two stage, air-cooled
50 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled intercooler, mounted with pressure relief valve
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 86”L x 74”W x 76”H, 2900 lbs

DS133 – 60 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 400 psig discharge at 12,000 SCFH flow

Skid mounted 2AN38F compressor, two stage, air-cooled
60 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled intercooler, mounted with pressure relief valve
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 86”L x 74”W x 76”H, 2900 lbs

DS192 - 40 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 200 psig discharge pressure at 18,300 SCFH flow

Skid mounted AN44F compressor, single stage, air-cooled
40 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 70”L x 74”W x 76”H, 2500 lbs

DS192 - 50 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 200 psig discharge pressure at 18,300 SCFH flow

Skid mounted AN44F compressor, single stage, air-cooled
50 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 70”L x 74”W x 76”H, 2500 lbs

DS303 – 50 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 200 psig discharge pressure at 28,600 SCFH flow

Skid mounted AN68F compressor, single stage, air-cooled
50 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 70”L x 74”W x 76”H, 2500 lbs

DS303 – 60 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 200 psig discharge pressure at 28,600 SCFH flow

Skid mounted AN68F compressor, single stage, air-cooled
60 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 70”L x 74”W x 76”H, 2500 lbs

DS303 – 75 HP Hycomp Odyssey Oil-Free Booster System

100 psig inlet to 200 psig discharge pressure at 28,600 SCFH flow

Skid mounted AN68F compressor, single stage, air-cooled
75 HP TEFC motor with adjustable base - 460 V / 3 Ph / 60 Hz
Motor contactor & overload protection
V-belt drive and belt guard
Air cooled aftercooler, mounted with pressure relief valve
Control panel with PLC with HMI touch screen
On screen pressure, temperature, and fault readings
Fully automatic compressor load/unload
E-Stop push button
Pressure transducers and RTD
Size/Weight: 70”L x 74”W x 76”H, 2500 lbs

